

SPECIFICATIONS

* FEATURES:

- * High Brightness.
- * External OSD key board.
- * Fast response time.
- * Low electromagnetic wave and power saver.
- * RoHS compliance.

Touch System	3MTouch ELO-Touch Screen	
LCD Panel	Size Pixel	15.0
	Pitch(mm)	0.297*0.297
	Backlight	LED
	Cell Type	TN
	Response	8ms
	Aspect Ratio	4:3
Viewing Angle	Horizontal	160°
	Vertical	140°
Video	Input Mode	XGA
	Horizontal	15~60KHz
	Vertical	48~75Hz
Display	Resolution	1024*768
	Contrast Ratio	700:1Typ
	Brightness	250cd/m2
	Horizontal Size	304.128
	Vertical Size	228.096
	Colors	16.2M
	Bandwidth	90MHz
	Consumption	15W max
Power	Management	VESA-DPMS 15W PowerDown Mode</=3Watts
	Input	AC/DC Adapter(Input 110-240VAC,Output 12 VDC/4A)
Operations	Function Key	5Key
	OSD Adjustment	Constrast,Brightness,Phase,Clock,H-position,V-position,....Exit
Input Signal		0.7Vpp Analog75 ohm
Sync		TTL Level Separate,Composite
Windows Compatibility		WindowsXP/2000
PC Interface		Analog Interface
Signal Cable		Standard VGA cable w/15-pin D-sub
EMI/Safety		
Operating Temperature		0°C~40°C
Humidity		10~85%
Outer Dimension		331x255x48